

RIVEER

ENVIRONMENTAL

THE CYCLONATOR II PRETREATMENT

PUSH BUTTON OPERATION

- FULL COMPUTER LOGIC ALLOWS FOR 1 TO 6 STAGE PRETREATMENT PROCESS WITH JUST THE PUSH OF A BUTTON



Exclusive CII Pretreatment System Features

- WASH AND RINSE ON THE SAME WASH PAD
- OIL COALESCING WITH AUTOMATIC OIL SKIMMER
- AUTOMATIC 24/7 OZONE INJECTION AND SYSTEM RECIRCULATION
- ALL STAINLESS STEEL CONSTRUCTION WITH ALLEN BRADLEY ELECTRICS, GOULDS PUMPS, AND SIEMENS BLOWER

PHOSPHATE RECYCLING SYSTEM

THE CYCLONATOR II

Save 80% or more in chemical costs by recycling and reusing your phosphate pretreatment solution. The Cyclonator II will collect and filter your solution, allowing you to reuse it instead of wasting it by going down the drain.

The Cyclonator II Filtration Specifications

Dimensions	48" W x 102" L x 50" H
Weight	1,200 Lbs. Dry
Capacity	800 Gallons
Electric	220V Single, 240, 480 Three-phase
Filtration	Oil/Water & Solids Separation 4 Stage to 5 Microns
Ozone Injection	Automatic 24/7 Corona discharge
Oil Coalescing	330 Ft ² Lantec® Polypropylene media
Oil Collection	Automatic belt type oil skimmer
Controls	Allen Bradley, NEMA 4, IEC rated, industrial controls
Process Rate	Over 12 GPM
Flow Rate	3-6 GPM

Riveer Environmental
233 Veterans Blvd. South Haven, MI 49090
888-857-7304 sales@riveer.com www.riveer.com/typhoon